

W. H. K. Bester

Scientific Computing 372

L^AT_EX §4: Tables and figures

Last updated: 19 February 2019



UNIVERSITEIT
iYUNIVESITHI
STELLENBOSCH
UNIVERSITY

100
1918 · 2018

Schedule

- 1 Introduction and setting text
- 2 Setting mathematics
- 3 Standard environments
- 4 **Tables and figures**
- 5 Boxes and new environments
- 6 AMS-LATEX
- 7 Beamer and PGF

Example (Matrices in mathematics mode)

- Use the array environment
- Separate columns with &
- End rows with \\

The matrix `\[`
`\begin{array}{clcr}`
`a+b+c & uv & x-y & 27 \\`
`a+b & u-v & z & 134 \\`
`a & 3u\times vw & xyz`
`& 2.978`
`\end{array} \]`
 is easy to produce.

The matrix

$$\begin{array}{clcr}
 a + b + c & uv & x - y & 27 \\
 a + b & u - v & z & 134 \\
 a & 3u \times vw & xyz & 2.978
 \end{array}$$

is easy to produce.

Nested arrays

Example (More with arrays)

Watch this:

```

\[\frac{
\left[\begin{array}{cc}
\left|\begin{array}{cc}
a & b \\
c & d
\end{array}\right| & 1 \\
2 & \sum_{i=1}^n x_i^2
\end{array}\right]}
{\begin{array}{ccc}
1 & 2 & 3 \\
4 & 5 & 6 \\
7 & 8 & 9
\end{array}}\]
Beautiful, yes?

```

Watch this:

$$\frac{\left[\begin{array}{cc|c} a & b & 1 \\ c & d & \sum_{i=1}^n x_i^2 \end{array} \right]}{\begin{array}{|ccc|} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{array}}$$

Beautiful, yes?

Example (Something else with arrays)

- Note that `\left` and `\right` have to be balanced

Thus, we have

```
\begin{eqnarray}
x & = & \left\{
\begin{array}{ll}
3z, & z \geq 0 \\
z+3, & 0 > z \geq -5 \\
2z+8, & z < -5
\end{array}
\right. \nonumber \\
y & = & \frac{z^2}{\sin z}.
\label{y}
\end{eqnarray}
```

Now, take (`\ref{y}`), and

Thus, we have

$$\begin{aligned}
 x &= \begin{cases} 3z, & z \geq 0 \\ z + 3, & 0 > z \geq -5 \\ 2z + 8, & z < -5 \end{cases} \\
 y &= \frac{z^2}{\sin z}. \tag{1}
 \end{aligned}$$

Now, take (1), and ...

Example (Tabular data)

- Use the tabular environment

```
\begin{tabular}{|p{2.6cm}||c|r|}  
\hline  
Subject & Prac & Tut \\  
\hline\hline  
Physics & 7 & 3 \\  
\hline  
Maths & None & 10 \\  
\cline{1-1}\cline{3-3}  
Computer Science, the best  
subject in the whole universe,  
but then again, I am  
biased & 5 & 5 \\  
\hline  
\end{tabular}
```

| Subject | Prac | Tut |
|---|------|-----|
| Physics | 7 | 3 |
| Maths | None | 10 |
| Computer Science, the best subject in the whole universe, but then again, I am biased | 5 | 5 |

Example (Multicolumn tabular data)

- Use `\multicolumn{<n>}{<align>}{<entry>}`, where `<n>` is the number of columns to spread over
- Also note the mischief I get up to with the `@{<text>}` column specifier

```
\begin{center}
\begin{tabular}{|l|l|r@{.}l|}
\hline
\multicolumn{2}{|c|}{Item} &
\multicolumn{2}{|c|}{Price} \\ \hline
Apples & (per dozen) & 12 & 99 \\
Onions & (each) & 0 & 75 \\ \hline
\end{tabular}
\end{center}
```

| Item | | Price |
|--------|-------------|-------|
| Apples | (per dozen) | 12.99 |
| Onions | (each) | 0.75 |

Column specifiers

- l Left-aligned items
- r Right-aligned items
- c Centred items
- @{<text>} Inserts <text> in every row; in math mode when in an array, left-to-right when in tabular
- p{<w>} Produces a justified paragraph box of width <w>

Horizontal lines

- `\hline` draws a line the full width of the environment
- `\cline{<c1>-<c2>}` draws a line from column <c1> to <c2>
- The columns are numbered 1, 2, ...

Example (Arbitrarily aligned items)

- Use the `tabbing` environment
- Set tabs with `\=`
- Move to next tab with `\>`
- End lines with `\\`

The environment starts on a new line, as follows.

```
\begin{tabbing}
When \= it rains, \= then \\
  \> the \> road is very, \\
  \> \> very wet! \\
  \> Don't slip\ldots.
\end{tabbing}
Afterwards, normal text
continues on a new line.
```

The environment starts on a new line, as follows.

```
When it rains, then
           the   road is very,
           very wet!
Don't slip....
```

Afterwards, normal text continues on a new line.

Figures and other floating bodies

- \TeX will happily break sentences over pages
- Things such as pictures cannot be split
- They must be “floated” to convenient places, like the top of a page, to prevent half-empty pages
- Use the `figure` environment for figures
- Use the `table` environment for tables
- Inside a floating environment, use `\caption{⟨text⟩}` for an automatically numbered caption
- The optional arguments `h` (here), `t` (top of page), `b` (bottom of page), and `p` (separate floats page) specifies where the float may be put

Floating bodies

Rules to determine where a float is put

- Placed in the earliest place that does not violate subsequent rules, except that `h` takes precedence over `t`
- Will not be printed on an earlier page than the environment appears
- No figure will be printed before an earlier figure; no table before an earlier table
- It may appear only at a position allowed by the optional arguments; `tbp` is assumed if the argument is missing
- Placement of a float cannot produce an overfull page

Example (Floating table)

- Note that the `\label` command must go inside or after the `\caption` command
- Where may the following be put?¹

```
\begin{table}[tb]
\begin{center}
\begin{tabular}{|c|c|}
\hline A silly & little table \\
\hline to illustrate & the point \\
\hline \end{tabular}\end{center}
\caption[Nice table]{A nice little table}
\label{t:nice}
\end{table}
```

¹top of page, bottom of page

A Table of ...

- `\tableofcontents`, `\listoffigures`, `\listoftables`
- The optional argument to `\caption` gives the text of the entry in the `listof` commands

Graphics

- Include the package `graphicx`
- Use the `\includegraphics` command

Text in the margins

- Use the `\marginpar [⟨right text⟩]{⟨left text⟩}` command